

---

**genomehubs**

*Release 2.4.10*

**genomehubs**

**May 12, 2022**



# CONTENTS

<b>1</b>	<b>GenomeHubs</b>	<b>1</b>
1.1	Installation . . . . .	1
1.2	Documentation . . . . .	1
1.3	Development . . . . .	1
<b>2</b>	<b>Installation</b>	<b>3</b>
<b>3</b>	<b>Usage</b>	<b>5</b>
<b>4</b>	<b>Reference</b>	<b>7</b>
4.1	init . . . . .	7
4.2	parse . . . . .	8
4.3	index . . . . .	9
4.4	fill . . . . .	11
<b>5</b>	<b>Contributing</b>	<b>15</b>
5.1	Bug reports . . . . .	15
5.2	Documentation improvements . . . . .	15
5.3	Feature requests and feedback . . . . .	15
5.4	Development . . . . .	15
<b>6</b>	<b>Authors</b>	<b>19</b>
<b>7</b>	<b>Changelog</b>	<b>21</b>
7.1	2.0.0 (2020-07-02) . . . . .	21
<b>8</b>	<b>Indices and tables</b>	<b>23</b>
	<b>Python Module Index</b>	<b>25</b>
	<b>Index</b>	<b>27</b>



## **GENOMEHUBS**

### **1.1 Installation**

```
conda install -c tolkit genomehubs
```

or

```
pip install genomehubs
```

You can also install the in-development version with:

```
pip install https://github.com/genomehubs/genomehubs/archive/main.zip
```

### **1.2 Documentation**

<https://genomehubs.readthedocs.io/>

### **1.3 Development**

To run all tests run:

```
tox
```



## INSTALLATION

At the command line:

```
pip install genomehubs
```





---

## CHAPTER THREE

---

### USAGE

To use genomehubs in a project:

```
import genomehubs
```



## REFERENCE

### 4.1 init

Initialise a GenomeHubs instance.

**Usage:**

```
genomehubs init [--hub-name STRING] [--hub-path PATH] [--hub-version PATH] [--config-file PATH...] [--config-save PATH] [--es-host URL...] [--es-url URL] [--insdc-metadata] [--insdc-root INT...] [--restore-indices] [--taxonomy-path PATH] [--taxonomy-source STRING] [--taxonomy-ncbi-root INT] [--taxonomy-ncbi-url URL] [--taxonomy-ott-root INT] [--taxonomy-ott-url URL] [--taxonomy-jsonl PATH] [--taxonomy-format STRING] [--taxonomy-root STRING] [--taxonomy-url URL] [--taxonomy-file PATH...] [--taxon-preload] [--docker-contain STRING...] [--docker-network STRING] [--docker-timeout INT] [--docker-es-container STRING] [--docker-es-image URL] [--reset] [--force-reset] [-h|-help] [-v|-version]
```

**Options:**

- hub-name** STRING    GenomeHubs instance name.
- hub-path** PATH    GenomeHubs instance root directory path.
- hub-version** STR    GenomeHubs instance version string.
- config-file** PATH    Path to YAML file containing configuration options.
- config-save** PATH    Path to write configuration options to YAML file.
- es-host** URL    Elasticsearch hostname/URL and port.
- es-url** URL    Remote URL to fetch Elasticsearch code.
- insdc-metadata**    Flag to index metadata for public INSDC assemblies.
- insdc-root** INT    Root taxid when indexing public INSDC assemblies.
- restore-indices**    Flag to restore taxon and assembly indices.
- taxonomy-path** DIR    Path to directory containing raw taxonomies.
- taxonomy-source** STRING    Name of taxonomy to use (ncbi or ott).
- taxonomy-ncbi-root** INT    Root taxid for NCBI taxonomy index.
- taxonomy-ncbi-url** URL    Remote URL to fetch NCBI taxonomy.
- taxonomy-ott-root** INT    Root taxid for Open Tree of Life taxonomy index.
- taxonomy-ott-url** URL    Remote URL to fetch Open Tree of Life taxonomy.
- taxonomy-format** STRING    Format of taxonomy (ncbi, ott). Newick support is planned.
- taxonomy-root** STRING    Root taxid.

**--taxonomy-file PATH** Taxonomy file names.  
**--taxonomy-url URL** Remote URL to fetch taxonomy.  
**--taxonomy-jsonl PATH** Path to JSON Lines format taxonomy file of additional taxa.  
**--taxon-preload** Flag to preload all taxa in taxonomy into taxon index.  
**--docker-contain STRING** GenomeHubs component to run in Docker.  
**--docker-network STRING** Docker network name.  
**--docker-timeout STRING** Time in seconds to wait for a component to start in Docker.  
**--docker-es-container STRING** ElasticSearch Docker container name.  
**--docker-es-image STRING** ElasticSearch Docker image name.  
**--reset** Flag to reset GenomeHubs instance if already exists.  
**--force-reset** Flag to force reset GenomeHubs instance if already exists.  
**-h, --help** Show this  
**-v, --version** Show version number

## Examples

# 1. New GenomeHub with default settings `./genomehubs init`  
 # 2. New GenomeHub in specified directory, populated with Lepidoptera assembly # metadata from INSDC `./genomehubs init --hub-path /path/to/GenomeHub --insdc-root 7088 --insdc-meta`  
`genomehubs.lib.init.add_jsonl_to_taxonomy(stream, jsonl)`  
 Add entries from JSON Lines format file to taxonomy stream.  
`genomehubs.lib.init.cli()`  
 Entry point.  
`genomehubs.lib.init.extend_lineage(entry)`  
 Add current taxon to beginning of lineage.  
`genomehubs.lib.init.main(args)`  
 Initialise genomehubs.  
`genomehubs.lib.init.process_subspecies(data)`  
 Find species name from subspecies and add to lineage.

## 4.2 parse

Parse a local or remote data source.

### Usage:

**genomehubs parse** [**--btk**] [**--btk-root STRING...**] [**--wikidata PATH**] [**--wikidata-root STRING...**] [**--wikidata-xref STRING...**] [**--gbif**] [**--gbif-root STRING...**] [**--gbif-xref STRING...**] [**--ncbi-datasets-genome PATH**] [**--outfile PATH**] [**--refseq-mitochondria**] [**--refseq-organelles**] [**--refseq-plastids**] [**--refseq-root NAME**] [**-h**|-help] [**-v**|-version]

### Options:

**--btk** Parse assemblies in BlobToolKit  
**--btk-root STRING** Scientific name of root taxon  
**--gbif** Parse taxa in GBIF  
**--gbif-root STRING** GBIF taxon ID of root taxon  
**--gbif-xref STRING** Include link to external reference from GBIF (e.g. NBN, BOLD)  
**--meta PATH** YAML format file of analysis metadata  
**--wikidata PATH** Parse taxa in WikiData dump  
**--wikidata-root STRING** WikiData taxon ID of root taxon  
**--wikidata-xref STRING** Include link to external reference from WikiData (e.g. NBN, BOLD)  
**--ncbi-datasets-genome PATH** Parse NCBI Datasets genome directory  
**--outfile PATH** Save parsed output to file  
**--refseq-mitochondria** Parse mitochondrial genomes from the NCBI RefSeq organelle collection  
**--refseq-organelles** Parse all genomes from the NCBI RefSeq organelle collection  
**--refseq-plastids** Parse plastid genomes from the NCBI RefSeq organelle collection  
**--refseq-root NAME** Name (not taxId) of root taxon  
**-h, --help** Show this  
**-v, --version** Show version number

`genomehubs.lib.parse.cli()`

Entry point.

`genomehubs.lib.parse.main(args)`

Parse data sources.

## 4.3 index

Index a file, directory or repository.

Usage:

**genomehubs index** [**--hub-name STRING**] [**--hub-path PATH**] [**--hub-version PATH**] [**--config-file PATH...**] [**--config-save PATH**] [**--es-host URL...**] [**--assembly-dir PATH**] [**--assembly-repo URL**] [**--assembly-exception PATH**] [**--feature-dir PATH**] [**--taxon-dir PATH**] [**--taxon-repo URL**] [**--taxon-exception PATH**] [**--taxon-lookup STRING**] [**--taxon-lookup-root STRING**] [**--taxon-lookup-in-memory**] [**--taxon-id-as-xref STRING**] [**--taxon-spellcheck**] [**--taxonomy-source STRING**] [**--file PATH...**] [**file-dir PATH...**] [**--remote-file URL...**] [**--remote-file-dir URL...**] [**--taxon-id STRING**] [**--assembly-id STRING**] [**--analysis-id STRING**] [**--file-title STRING**] [**--file-description STRING**] [**--file-metadata PATH**] [**--dry-run**] [**-h**|-**help**] [**-v**|-**version**]

Options:

**--hub-name STRING** GenomeHubs instance name.  
**--hub-path PATH** GenomeHubs instance root directory path.  
**--hub-version STR** GenomeHubs instance version string.

**--config-file PATH** Path to YAML file containing configuration options.

**--config-save PATH** Path to write configuration options to YAML file.

**--es-host URL** Elasticsearch hostname/URL and port.

**--assembly-dir PATH** Path to directory containing assembly-level data.

**--assembly-repo URL** Remote git repository containing assembly-level data. Optionally include *~branch-name* suffix.

**--assembly-exception PATH** Path to directory to write assembly data that failed to import.

**--feature-dir PATH** Path to directory containing feature-level data.

**-taxon-lookup-root STRING** Root taxon Id for in-memory lookup. **-taxon-lookup STRING** Taxon name class to lookup (scientific|any). [Default: scientific] **-taxon-lookup-in-memory** Flag to use in-memory taxon name lookup. **-taxon-id-as-xref STRING** Set source DB name to treat taxon\_id in file as xref. **-taxon-spellcheck** Flag to use fuzzy matching to match taxon names. **-taxon-dir PATH** Path to directory containing taxon-level data. **-taxon-repo URL** Remote git repository containing taxon-level data.

Optionally include *~branch-name* suffix.

**--taxon-exception PATH** Path to directory to write taxon data that failed to import.

**--taxonomy-source STRING** Name of taxonomy to use (ncbi or ott).

**--file PATH** Path to file for generic file import.

**--file-dir PATH** Path to directory containing generic files to import.

**--remote-file URL** Location of remote file for generic file import.

**--remote-file-dir URL** Location of remote directory containing generic files to import.

**--taxon-id STRING** Taxon ID to index files against.

**--assembly-id STRING** Assembly ID to index files against.

**--analysis-id STRING** Analysis ID to index files against.

**--file-title STRING** Default title for indexed files.

**--file-description STRING** Default description for all indexed files.

**--file-metadata PATH** CSV, TSV, YAML or JSON file metadata with one entry per file to be indexed.

**--dry-run** Flag to run without loading data into the elasticsearch index.

**-h, --help** Show this

**-v, --version** Show version number

## Examples

```
# 1. Index all files in a remote repository ./genomehubs index -taxon-repo https://github.com/genomehubs/goat-data
genomehubs.lib.index.cli()
    Entry point.

genomehubs.lib.index.convert_features_to_docs(with_ids)
    Convert features to docs.
```

`genomehubs.lib.index.group_rows`(*taxon\_id, rows, with\_ids, without\_ids, taxon\_asm\_data, imported\_rows, types, failed\_rows, blanks*)

Group processed rows by available taxon info for import.

`genomehubs.lib.index.index_assembly_records`(*es, taxonomy\_name, opts, with\_ids, blanks, taxon\_types, taxon\_asm\_data*)

Index an assembly records.

`genomehubs.lib.index.index_feature_records`(*es, opts, taxonomy\_name, with\_ids, blanks*)

Index a feature records.

`genomehubs.lib.index.index_features`(*es, opts, \*, dry\_run=False*)

Index assembly features.

`genomehubs.lib.index.index_file`(*es, types, names, data, opts, \*, taxon\_table=None, shared\_values=None*)

Index a file.

`genomehubs.lib.index.index_taxon_assembly`(*es, opts, index='taxon', \*, dry\_run=False, taxonomy\_name*)

Call taxon- or assembly-specific indexing functions.

`genomehubs.lib.index.index_taxon_records`(*es, taxonomy\_name, opts, with\_ids, blanks, types*)

Index a taxon records.

`genomehubs.lib.index.main`(*args*)

Index files.

`genomehubs.lib.index.not_blank`(*key, obj, blanks*)

Test value is not blank.

`genomehubs.lib.index.process_taxon_assembly_records`(*es, taxonomy\_name, opts, processed\_rows, with\_ids, blanks, taxon\_asm\_data, imported\_rows, types, failed\_rows, header, taxon\_table, taxon\_types*)

Process taxon and assembly records.

`genomehubs.lib.index.set_feature_types`(*types*)

Set types for feature properties.

`genomehubs.lib.index.summarise_imported_taxa`(*docs, imported\_taxa*)

Summarise taxon information from a stram of taxon docs.

## 4.4 fill

Fill attribute values.

Usage:

```
genomehubs fill [-hub-name STRING] [-hub-path PATH] [-hub-version PATH] [-config-file PATH...]
               [-config-save PATH] [-es-host URL...] [-taxonomy-source STRING] [-traverse-limit STRING]
               [-traverse-infer-ancestors] [-traverse-infer-descendants] [-traverse-infer-both] [-traverse-threads INT]
               [-traverse-depth INT] [-traverse-root STRING] [-traverse-weight STRING] [-h|-help] [-v|-version]
```

Options:

**--hub-name STRING** GenomeHubs instance name.

**--hub-path PATH** GenomeHubs instance root directory path.

**--hub-version STR** GenomeHubs instance version string.  
**--config-file PATH** Path to YAML file containing configuration options.  
**--config-save PATH** Path to write configuration options to YAML file.  
**--es-host URL** Elasticsearch hostname/URL and port.  
**--taxonomy-source STRING** Name of taxonomy to use (ncbi or ott).  
**--traverse-depth INT** Maximum depth for tree traversal relative to root taxon.  
**--traverse-infer-ancestors** Flag to enable tree traversal from tips to root.  
**--traverse-infer-descendants** Flag to enable tree traversal from root to tips.  
**--traverse-infer-both** Flag to enable tree traversal from tips to root and back to tips.  
**--traverse-limit STRING** Maximum rank to ascend to during traversal. [Default: null]  
**--traverse-root ID** Root taxon id for tree traversal.  
**--traverse-threads INT** Number of threads to use for tree traversal. [Default: 1]  
**--traverse-weight STRING** Weighting scheme for setting values during tree traversal.  
**-h, --help** Show this  
**-v, --version** Show version number

## Examples

# 1. Traverse tree up to taxon\_id 7088 ./genomehubs fill --traverse-root 7088

`genomehubs.lib.fill.apply_summary(summary, values, *, primary_values=None, summary_types=None, max_value=None, min_value=None, order=None)`

Apply summary statistic functions.

`genomehubs.lib.fill.cli()`

Entry point.

`genomehubs.lib.fill.copy_attribute_summary(source, meta)`

Copy an attribute summary, removing values.

`genomehubs.lib.fill.deduped_list(arr)`

Remove duplicate values from a list.

`genomehubs.lib.fill.deduped_list_length(arr)`

Find number of unique values in a list.

`genomehubs.lib.fill.earliest(arr, *args)`

Select earliest date from a list.

`genomehubs.lib.fill.enum(tup)`

Use list index to prioritise values.

`genomehubs.lib.fill.flatten_list(arr)`

Flatten a list by expanding any nested lists.

`genomehubs.lib.fill.get_max_depth(es, *, index)`

Find max depth of root lineage.



`genomehubs.lib.fill.get_max_depth_by_lineage(es, *, index, root)`  
Find max depth of specified root lineage.

`genomehubs.lib.fill.latest(arr, *args)`  
Select earliest date from a list.

`genomehubs.lib.fill.main(args)`  
Initialise genomehubs.

`genomehubs.lib.fill.range(arr)`  
Calculate difference between max and min values.

`genomehubs.lib.fill.set_aggregation_source(attribute, source=None)`  
Set attribute aggregation source.

`genomehubs.lib.fill.set_attributes_to_descend(meta, traverse_limit)`  
Set which attributes should have values inferred from ancestral taxa.

`genomehubs.lib.fill.set_traverse_values(summaries, values, primary_values, max_value, min_value, meta, attribute, value_type, traverse, source)`  
Set values use for tree traversal.

`genomehubs.lib.fill.set_values_from_descendants(*, attributes, descendant_values, meta, taxon_id, parent, taxon_rank, traverse_limit, parents, descendant_ranks=None, attr_dict=None, limits=None)`  
Set attribute summary values from descendant values.

`genomehubs.lib.fill.stream_descendant_nodes_missing_attributes(es, *, index, attributes, root, size=10)`  
Get entries descended from root that lack one or more attributes.

`genomehubs.lib.fill.stream_missing_attributes_at_level(es, *, nodes, attrs, template, level=1)`  
Stream all descendant nodes with missing attributes.

`genomehubs.lib.fill.stream_nodes_by_root_depth(es, *, index, root, depth, size=10)`  
Get entries by depth of root taxon.

`genomehubs.lib.fill.summarise_attribute_values(attribute, meta, *, values=None, max_value=None, min_value=None, source='direct')`  
Calculate a single summary value for an attribute.

`genomehubs.lib.fill.summarise_attributes(*, attributes, attrs, meta, parent, parents)`  
Set attribute summary values.

`genomehubs.lib.fill.track_descendant_ranks(node, descendant_ranks)`  
Keep track of descendant ranks.

`genomehubs.lib.fill.track_missing_attribute_values(node, missing_attributes, attr_dict, desc_attrs, desc_attr_limits)`  
Keep track of missing attribute values for in memory traversal.

`genomehubs.lib.fill.traverse_from_root(es, opts, *, template, root=None, max_depth=None, log=True)`  
Traverse a tree, filling in values.

`genomehubs.lib.fill.traverse_from_tips(es, opts, *, template, root=None, max_depth=None)`  
Traverse a tree, filling in values.

`genomehubs.lib.fill.traverse_handler(es, opts, template)`

Handle single or multi-threaded tree traversal.

`genomehubs.lib.fill.traverse_helper(params)`

Wrap `traverse_tree` for multithreaded traversal.

`genomehubs.lib.fill.traverse_tree(es, opts, template, root, max_depth)`

Propagate values by tree traversal.

## CONTRIBUTING

### 5.1 Bug reports

When [reporting a bug](#) please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

### 5.2 Documentation improvements

Contributions to the official `genomehubs` docs and internal docstrings are always welcome.

### 5.3 Feature requests and feedback

The best way to send feedback is to file an issue at <https://github.com/genomehubs/genomehubs/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that code contributions are welcome

### 5.4 Development

To install the development version of *genomehubs*:

1. Clone the *genomehubs* repository:

```
git clone https://github.com/genomehubs/genomehubs
```

2. Install the dependencies using pip:

```
cd genomehubs  
pip install -r requirements.txt
```

3. Build and install the *genomehubs* package:

```
python3 setup.py sdist bdist_wheel \  
&& echo y | pip uninstall genomehubs \  
&& pip install dist/genomehubs-2.0.0-py3-none-any.whl
```

To set up *genomehubs* for local development:

1. Fork *genomehubs* <<https://github.com/genomehubs/genomehubs>> - (look for the “Fork” button).
2. Clone your fork locally:

```
git clone git@github.com:USERNAME/genomehubs.git
```

3. Create a branch for local development:

```
git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

4. When you’re done making changes run all the checks and docs builder with *tox* one command:

```
tox
```

5. Commit your changes and push your branch to GitHub:

```
git add .  
git commit -m "Your detailed description of your changes."  
git push origin name-of-your-bugfix-or-feature
```

6. Submit a pull request through the GitHub website.

## 5.4.1 Pull Request Guidelines

If you need some code review or feedback while you’re developing the code just make the pull request.

For merging, you should:

1. Include passing tests (run *tox*)<sup>1</sup>.
2. Update documentation when there’s new API, functionality etc.
3. Add a note to *CHANGELOG.rst* about the changes.
4. Add yourself to *AUTHORS.rst*.

---

<sup>1</sup> If you don’t have all the necessary python versions available locally you can rely on Travis - it will *run the tests* for each change you add in the pull request.

It will be slower though ...

### 5.4.2 Tips

To run a subset of tests:

```
tox -e envname -- pytest -k test_myfeature
```

To run all the test environments in *parallel*:

```
tox -p
```



## AUTHORS

- Richard Challis - <https://twitter.com/rjchallis>
- Sujai Kumar - <https://twitter.com/sujaik>





## CHANGELOG

### 7.1 2.0.0 (2020-07-02)

- First release on PyPI.



## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`



## PYTHON MODULE INDEX

### g

`genomehubs.lib.fill`, 11  
`genomehubs.lib.index`, 9  
`genomehubs.lib.init`, 7  
`genomehubs.lib.parse`, 8



## A

`add_jsonl_to_taxonomy()` (in module `genomehubs.lib.init`), 8  
`apply_summary()` (in module `genomehubs.lib.fill`), 12

## C

`cli()` (in module `genomehubs.lib.fill`), 12  
`cli()` (in module `genomehubs.lib.index`), 10  
`cli()` (in module `genomehubs.lib.init`), 8  
`cli()` (in module `genomehubs.lib.parse`), 9  
`convert_features_to_docs()` (in module `genomehubs.lib.index`), 10  
`copy_attribute_summary()` (in module `genomehubs.lib.fill`), 12

## D

`deduped_list()` (in module `genomehubs.lib.fill`), 12  
`deduped_list_length()` (in module `genomehubs.lib.fill`), 12

## E

`earliest()` (in module `genomehubs.lib.fill`), 12  
`enum()` (in module `genomehubs.lib.fill`), 12  
`extend_lineage()` (in module `genomehubs.lib.init`), 8

## F

`flatten_list()` (in module `genomehubs.lib.fill`), 12

## G

`genomehubs.lib.fill`  
 module, 11  
`genomehubs.lib.index`  
 module, 9  
`genomehubs.lib.init`  
 module, 7  
`genomehubs.lib.parse`  
 module, 8  
`get_max_depth()` (in module `genomehubs.lib.fill`), 12  
`get_max_depth_by_lineage()` (in module `genomehubs.lib.fill`), 12  
`group_rows()` (in module `genomehubs.lib.index`), 10

## I

`index_assembly_records()` (in module `genomehubs.lib.index`), 11  
`index_feature_records()` (in module `genomehubs.lib.index`), 11  
`index_features()` (in module `genomehubs.lib.index`), 11  
`index_file()` (in module `genomehubs.lib.index`), 11  
`index_taxon_assembly()` (in module `genomehubs.lib.index`), 11  
`index_taxon_records()` (in module `genomehubs.lib.index`), 11

## L

`latest()` (in module `genomehubs.lib.fill`), 13

## M

`main()` (in module `genomehubs.lib.fill`), 13  
`main()` (in module `genomehubs.lib.index`), 11  
`main()` (in module `genomehubs.lib.init`), 8  
`main()` (in module `genomehubs.lib.parse`), 9  
 module  
   `genomehubs.lib.fill`, 11  
   `genomehubs.lib.index`, 9  
   `genomehubs.lib.init`, 7  
   `genomehubs.lib.parse`, 8

## N

`not_blank()` (in module `genomehubs.lib.index`), 11

## P

`process_subspecies()` (in module `genomehubs.lib.init`), 8  
`process_taxon_assembly_records()` (in module `genomehubs.lib.index`), 11

## R

`range()` (in module `genomehubs.lib.fill`), 13

## S

`set_aggregation_source()` (in module `genomehubs.lib.fill`), 13

[set\\_attributes\\_to\\_descend\(\)](#) (in module *genomehubs.lib.fill*), 13  
[set\\_feature\\_types\(\)](#) (in module *genomehubs.lib.index*), 11  
[set\\_traverse\\_values\(\)](#) (in module *genomehubs.lib.fill*), 13  
[set\\_values\\_from\\_descendants\(\)](#) (in module *genomehubs.lib.fill*), 13  
[stream\\_descendant\\_nodes\\_missing\\_attributes\(\)](#) (in module *genomehubs.lib.fill*), 13  
[stream\\_missing\\_attributes\\_at\\_level\(\)](#) (in module *genomehubs.lib.fill*), 13  
[stream\\_nodes\\_by\\_root\\_depth\(\)](#) (in module *genomehubs.lib.fill*), 13  
[summarise\\_attribute\\_values\(\)](#) (in module *genomehubs.lib.fill*), 13  
[summarise\\_attributes\(\)](#) (in module *genomehubs.lib.fill*), 13  
[summarise\\_imported\\_taxa\(\)](#) (in module *genomehubs.lib.index*), 11

## T

[track\\_descendant\\_ranks\(\)](#) (in module *genomehubs.lib.fill*), 13  
[track\\_missing\\_attribute\\_values\(\)](#) (in module *genomehubs.lib.fill*), 13  
[traverse\\_from\\_root\(\)](#) (in module *genomehubs.lib.fill*), 13  
[traverse\\_from\\_tips\(\)](#) (in module *genomehubs.lib.fill*), 13  
[traverse\\_handler\(\)](#) (in module *genomehubs.lib.fill*), 13  
[traverse\\_helper\(\)](#) (in module *genomehubs.lib.fill*), 14  
[traverse\\_tree\(\)](#) (in module *genomehubs.lib.fill*), 14